

Patent App. Number 09/751,160
Attorney Docket No.: PA00-1010-Y
Page 2 of 2

MARKED VERSION OF CLAIMS

1. (Currently Amended). A composition for coating a surface comprising (a) a solution of polyethylene oxide in water, wherein the polyethylene oxide has a molecular weight greater than 250,000, and (b) a surfactant, wherein the composition is capable of being removed from the surface at about room temperature with a solvent.
2. (Cancelled)
3. (Currently Amended). The composition according to claim 1 ~~or claim 2~~, wherein the solvent is water.
4. (Original) The composition according to claim 1, wherein the polyethylene oxide concentration is about 0.01 to 50 weight percent.
5. (Currently Amended) The composition according to claim ~~3~~1, wherein the surfactant is an anionic surfactant.
6. (Original) The composition according to claim 1, wherein the polyethylene oxide is a high molecular weight polyethylene oxide.
7. (Cancelled)
8. (Currently Amended) The composition according to claim 1, wherein the polyethylene oxide is of a molecular weight in the range of about ~~100,000~~250,000 to 8,000,000.
9. (Currently Amended) The composition according to claim 1 ~~or claim 2~~, further comprising a coloring agent.
10. (Currently Amended) The composition according to claim 1 ~~or claim 2~~, further comprising a fragrancng agent.

Patent App. Number 09/751,160
Attorney Docket No.: PA00-1010-Y
Page 3 of 3

11. (Currently Amended) The composition according to claim 1 ~~or claim 2~~, further comprising an anti-microbial agent.
12. (Currently Amended) The composition according to claim 1 ~~or claim 2~~, further comprising an anti-soiling agent.
13. (Original) The composition according to claim 12, wherein the anti-soiling agent is a detergent.
14. (Original) The composition according to claim 12, wherein the anti-soiling agent concentration is about 0.01 to 99.9 weight percent.
15. (Withdrawn) The composition according to claim 2, wherein the water soluble ether is one selected from the group comprising (hydroxypropyl cellulose, sodium carboxymethylcellulose, carboxymethyl hydroxyethyl cellulose, and hydroxyethyl cellulose).
16. (Withdrawn) A process of coating a surface comprising the step of: (a) applying the composition of claim 1 or claim 2 to the surface.
17. (Withdrawn) The process of claim 16, further comprising the step of: (b) drying the surface after coating step (a).
18. (Withdrawn) The process according to claim 17, wherein the drying step is conducted at about 1-250 degrees Centigrade.
19. (Withdrawn) The process according to claim 16, further comprising the step of: removing the coating by applying an aqueous solution to the coated surface.
20. (Withdrawn) The process according to claim 19, wherein the aqueous solution is water.

Patent App. Number 09/751,160
Attorney Docket No.: PA00-1010-Y
Page 4 of 4

21. (Withdrawn) The process according to claim 20, wherein the solution is at a temperature of about less than 85 degrees Centigrade.
22. (Withdrawn) The process according to claim 16 further comprising step of: applying an additional amount of the composition of claim 1 or claim 2 to the surface.
23. (Withdrawn) The process according to claim 16, wherein the surface is inanimate.
24. (Withdrawn) The process according to claim 16, wherein the surface is animate.
25. (Withdrawn) The process according to claim 24, wherein the animate surface is human skin.
26. (Withdrawn) An article of manufacture comprising a surface treated with the composition of claim 1 or claim 2.
27. (Not Entered)
28. (Not Entered)
29. (Not Entered)
30. (New) The composition according to Claim 1, wherein the Polyethylene Oxide is Ethylene Dioxide.
31. (New) The composition according to Claim 1, wherein the Polyethylene Oxide is Carboxymethyl Hydroxyethyl Cellulose.
32. (New) The composition according to Claim 1, wherein the Polyethylene Oxide is Hydroxyethyl Cellulose.
33. (New) The composition according to Claim 1, wherein the surfactant is Dodecyl Benzene Sulfonate.